



Technical Data Sheet

40% Sodium Bisulfite, Low Iron™

Property	Minimum	Maximum	on COA
NaHSO ₃ , % by Weight	38.0	42.0	✓
Specific Gravity at 20°C	1.31	1.38	✓
pH	3.8	5.0	✓
SO ₂ available, wt. %	23.4	25.8	
Iron, as Fe, ppm		5	
Sulfate, as Na ₂ SO ₄ , wt. %		0.3	

- 40% Sodium Bisulfite, Low Iron™ is a clear, colorless to pale yellow solution with a pungent odor
- NSF/ANSI/CAN 60 Certified
- Maximum use in potable water is 46 mg/L
- Maximum residual in finished drinking water is 0.1 m/L
- For information on safety and handling, consult the Safety Data Sheet (SDS) from Heimbürger & Company, Inc.

The information above is believed to be accurate and represents the best information currently available to us. However, Heimbürger & Company makes no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their purposes. In no event shall Heimbürger & Company be liable for any claims, losses or damages, howsoever arising, even if Heimbürger & Company has been advised of the possibility of such damages. The vendor assumes no responsibility for injury or damages resulting from the inappropriate alteration or manipulation of this Technical Data Sheet (TDS) and its contents from that originally submitted by Heimbürger & Company.